MARTCARE® FACESHIELD PREMIUM

PRODUCT CODE: AFP061-230-400

GREY BROWGUARD WITH POLYCARBONATE VISOR AND WHEEL RATCHET ADJUSTMENT

TECHNICAL SPECIFICATION

MARTCARE® RANGE

INSTRUCTIONS FOR USE

Before use, the browguard should be fitted to the visor

In use, ensure that the Faceshield fits comfortably and securely on the head

Ensure that the visor is in place before entering the hazard area



Browguard: Polypropylene

Wheel Ratchet Harness: Polythene, ABS, Nylon and Steel Fittings

Elastic Harness: Polythene, ABS, Nylon and Elasticated Strap

Visor: Polycarbonate



DIMENSIONS OF OUTER PACKAGING

Quantity: 10

Height: 392mm

Width: 216mm

Length: 362mm

Weight: 3.8Kg (Approx.)

CONFORMITY

Meets the requirements of EN 166.1.B.3.9 and EN 169

EC Certificate Number 2406, issued by BSi Product Certification

FACESHIELD FEATURES & PERFORMANCE

Offers protection against medium energy high speed particles at 120m/s (270mph), liquid droplets and molten metal

The optical qualities of the visor comply with the requirements of optical class 1 (highest)

Browguard with polycarbonate visor with wheel ratchet adjustment

Height: 117mm

DIMENSIONS OF FACESHIELD

Width: 215mm

Length: 384mm

Weight: 309g (Approx.)

CLEANING & MAINTENANCE

The browguard may be cleaned with soap and warm water and dried with a soft cloth

Do not clean with chemical or abrasive cleaners

The eye shield should be stored out of direct sunlight, away from chemicals and not exposed to extremes of temperature

LIMITATIONS OF USE

Protection will only be offered if the faceshield is fitted If the faceshield becomes scratched or damaged they should be

Do not apply paint, solvents, adhesives or self-adhesive labels, except in accordance with instructions from the manufacturer

The harness, when in contact with the skin may cause allergic reactions to susceptible individuals. If this occurs leave the hazard area, remove the faceshield and seek medical advice

Polycarbonate visors are not suitable for use with all chemicals - if you are unsure contact your supplier or JSP for help and advice

















