

# TECHNICAL SPECIFICATION



## EVO®3 Micro Peak Revolution® Wheel Ratchet Non Vented Linesman

White / AJG240-000-100



### DESCRIPTION

The EVO®3 Comfort Plus helmet combines a super strong shell for superior all day protection in the widest range of environments, with the comfort benefits of the new Evolution® 3D Adjustment™ harness system. EVO®3 is a true evolution of the long-established MK®2 and MK®3 helmets. The EVO®3 retains the JSP signature styling while incorporating developments first seen in the EVO®8. Packed full of the latest protection technology and features.

### OPTIONS

Blue (AJG240-000-500)  
Orange (AJG240-000-800)  
Red (AJG240-000-600)  
**White (AJG240-000-100)**  
Yellow (AJG240-000-200)

### SAFETY STANDARDS

EN 397 • EN 50365



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.






















Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jsp-safety.com / Web: www.jsp-safety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jsp-safety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 3 / Issued 28 Feb 2024 / Copyright 2018 - 2024. JSP Limited. All Rights Reserved.



## SPECIFICATIONS

	Peak Micro		Impact Resistance 50 Joules
	EN 50365 ELECTRICAL INSULATION 1000V		Resistance to Molten Metals and Hot Solids Helmets (optional) Yes
	Minimum Temperature -40°C		Maximum Temperature +50°C
	HDPE Shell Yes		Recyclable Shell
	Textile Harness		Depth Adjustment 3D Harness
	Wheel Ratchet Yes		Universal Accessories Slot Yes
	Ventilation No		Reflective Option Optional
	Integrated Eyewear Optional		ID card holder Optional
	BSI Kitemark Yes		Optional 4 point chinstrap (EN397 Compliant) Fitted
	JSPCheck Yes		Product Weight 403g
	Size 53-64cm		

## FEATURES



### Firmest Fit Available

The deep nape strap enables the firmest retention of any helmet, keeping it firmly rooted on the head. Available with either the Revolution® wheel ratchet or the OneTouch™ slip ratchet.



### CR2™ Reflective

Using Class RA2, high intensity reflective. CR2™ is the biggest step-up in night time visibility/reflectivity of head protection to date. Conforms to Class RA2, EN12899-1.



### Supreme Comfort

A 6-point textile cradle harness system & Chamlon™ cotton sweatband offer unrivalled comfort.



### 3D Adjustment

The comfortable textile harness features unique 1-2-3 point depth settings, offering the most precise fit attainable on an industrial safety helmet.



### Accessories

A universal attachment slot enables firm fitting of a range of Surefit™ safety visors and ear defenders. EVOSpec® Integrated eyewear is also available.



### JSP Logo Express®

Strengthen your corporate identity by applying a company logo on a range of our safety helmets. Minimum order quantities and set-up charges apply.

## LOGO

- Front
- Back

## RANGE



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jsp-safety.com / Web: www.jsp-safety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jsp-safety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 3 / Issued 28 Feb 2024 / Copyright 2018 - 2024. JSP Limited. All Rights Reserved.

