



AS320C (Ridgeway)

Standard	EN ISO 20345:2022+A1:2024
----------	---------------------------

Category	S7S FO HRO SR (ESD)
----------	---------------------

Size Range	UK 6 - 13 EU 40 - 48
------------	------------------------

Colour	Black
--------	-------

Slip Resistance	SR
-----------------	----

VEGAN
FRIENDLY

AS320C (Ridgeway): Ridgeway is a waterproof metal-free safety hiker. The upper is made from a rip-stop material with embossed Thermo-plastic Polyurethane (TPU) support. It features a breathable waterproof membrane and mesh inner lining. It has a fibre glass composite toe cap with 200 joules impact resistance. It comes with a removable moulded polyurethane (PU) footbed. The non-metallic midsole offers anti-penetration to min. 1100N. The Ethylene-Vinyl Acetate (EVA)/Rubber outsole is highly durable and features an excellent grip cleated rubber outsole for slip resistance. The boot features a smart and speedy fastening lacing system.

Upper	Rip-stop With Embossed TPU Support	Construction	Cemented
Inner Lining	Breathable waterproof membrane and mesh	Outsole	EVA/Rubber
Footbed	Removable Moulded PU	Weight	680 Grams (Half pair of size 8)
Impact Resistance	200 Joules Fibre Glass Composite Toe Cap	Penetration Resistance	Anti-penetration Non-Metallic Midsole - Min. 1100N

FEATURES

- ◆ Moulded TPU Toe Guard for Extra Durability
- ◆ Moulded TPU Heel Counter for Enhanced Heel Support and Extra Protection
- ◆ Deep padded mesh collar for extra comfort
- ◆ Outsole heat resistant to 300°C
- ◆ Oil resistant outsole
- ◆ Energy absorbing heel
- ◆ Smart & Speedy Fastening Lacing System
- ◆ Excellent grip cleated rubber outsole for slip resistance
- ◆ Non-leather upper
- ◆ Antistatic boot
- ◆ Electrostatic Discharge - Dissipative (ESD)

Care Advice: To enhance the life & performance of the footwear, upper should be kept clean & dry. Dry/damp cloth or shoe polish/spray to be used as per the need. Sole to be checked and clean regularly to maintain its traction. Any obvious damage in footwear may reduce full protection and must be replaced.