



AS966C (Demolition)

Standard	EN ISO 20345:2022+AI2024
Category	S7S CI FO SC LG HRO SR
Size Range	UK 6 - 13 EU 40 - 48
Colour	Stone
Slip Resistance	SR



AS966C (Demolition): Rugged and lightweight metal free 6" safety boot, with a water resistant full grain leather upper, and internal waterproof membrane. Thinsulate lined for thermal insulation. Heavy moulded rubber toe guard for extra durability tested to New Scuff Cap Standard (SC). Heavy moulded rubber heel counter for enhanced heel support and extra protection. A deep padded mesh collar gives extra comfort. Comfortable, cushioned and removable PU footbed with arch support for all day comfort. Phylon midsole enhances comfort and provides shock absorption.

Upper	Premium Nubuck Full Grain Cow Leather	Construction	Cemented
Inner Lining	Breathable waterproof membrane and mesh	Outsole	Phylon/Rubber
Footbed	Removable moulded PU	Weight	750 Grams (Half Pair UK Size 8)
Impact Resistance	200 Joules Fibre Glass Composite Toe Cap	Penetration Resistance	Anti-penetration Non-Metallic Midsole - Min. II/ON

FEATURES

- ◆ Rugged and lightweight metal free 6" safety boot
- ◆ Freelock lacing system for easy on/off
- ◆ Heavy Moulded Rubber Toe Guard for Extra Durability Tested to New Scuff Cap Standard (SC)
- ◆ Heavy moulded rubber heel counter for enhanced heel support and extra protection
- ◆ Comfortable, cushioned and removable PU footbed
- ◆ with arch support
- ◆ Phylon midsole enhances comfort and shock absorption
- ◆ Energy absorbing heel
- ◆ Outsole heat resistant to 300 Degrees
- ◆ Oil resistant outsole
- ◆ Antistatic boot

Care Advice: To enhance the life & performance of the footwear, upper should be kept clean & dry. Dry/damp cloth or shoe polish/spray to be used as per the need. Sole to be checked and clean regularly to maintain its traction. Any obvious damage in footwear may reduce full protection and must be replaced.