EVOLITE®

MIDPEAK - SLIP RATCHET - VENTILATED

TECHNICAL SPECIFICATION

HEAD PROTECTION

High strength engineering grade ABS which has been UV

Stabilised

PRODUCT CODE: AJB160-00 - 00

THE LIGHTEST SAFETY HELMET AVAILABLE IN EUROPE

INSTRUCTIONS FOR USE

Fit helmet on head and fasten strap to ensure fit

For adequate protection this helmet must be worn with peak facing forward

Ensure the helmet is adjusted to the size of the user's head

WEBBING HARNESS:

HDPE Strap & Webbing Clips with Polyester Webbing Straps

CHAMLON™ SWEATBAND:

Egyptian cotton core with porous PU coating for maximum sweat absorption. PH neutral, dermatologically tested



SLIP RATCHET: One Touch™ Slip Ratchet version of the EVOLite® is so simple to fir that it can be adjusted with just





CLEANING & MAINTENANCE

The unit may be cleaned with soap and warm water and dried with a soft cloth

The helmet should not be cleaned with chemical or abrasive

The helmet should be stored out of direct sunlight

The helmet should be stored away from chemicals and extremes of temperature

CONFORMITY

EN 397 & ΓΟCT P 50460-92 for Industrial Safety Helmets

EU Type Examination Certificate number 676976

Meets optional Lateral Deformation performance

Wide size range. Slip or wheel ratchet - High comfort fit

Available vented. Available with mid or micro peak

Company personalisation available by printing

DISCLAIMER: Information presented within this technical specification was correct on date of issue. Information may be subject to change without notice as part of ongoing product improvement and development. To confirm any specific piece of information shown is current please email technical@jspsafety.com .



















MIDPEAK - SLIP RATCHET - VENTILATED

TECHNICAL **SPECIFICATION**

HEAD PROTECTION

PRODUCT CODE: AJB160-00 - 00

THE LIGHTEST SAFETY HELMET AVAILABLE IN EUROPE

DIMENSIONS OF OUTER PACKAGING

Quantity: 10

Weight: 3.2kg (Approx.)



DIMENSIONS OF HELMET

Size: 530 - 640mm

Weight: 299g (Approx.)



HELMET COLOURS

Insert the following two digit number in place of the dashes in the product code of your desired helmet





01 White 02 Yellow



03 Green



05 Blue



06 Red







HELMET FEATURES

ILLINET I LATORILO		
EN STANDARD	EN397	Yes
PERFORMANCE	Impact Resistance Lateral Deformation	Yes 50 Joules Yes
TEMPERATURE RESISTANCE	+50°C Low Temperature	Yes Yes: EN397 -30°C FOCT P 50460-92 -30°C
SHELL MATERIAL	ABS Recyclable UV Stabilised	Yes Yes Yes
HARNESS MATERIAL	HDPE Textile	Yes Yes
OPTIONS	Universal Accessories Reflective CR2 option Integrated Eyewear Micro Peak	Yes Yes Yes Yes
HARNESS SYSTEM OPTIONS	JSP 3D Slip Ratchet 6 pts	Yes Yes Yes
CHINSTRAP OPTIONS	4 pts 2 pts	Yes Yes
LOGO OPTIONS	Front Rear Side MOQ Logo Individual Name	Yes Yes Yes 10 Yes

LIMITATIONS OF USE

Protection will only be offered if the helmet is fitted correctly

Any helmet subjected to severe impact should be replaced immediately. Do not apply paint, solvents or adhesive labels except in accordance with instructions from the manufacturer

The harness, when in contact with the skin may cause allergic reactions to susceptible individuals. If this occurs leave the hazard area, remove the helmet and seek medical

The attention of users is also drawn to the dangers of modifying or removing any of the original component parts, other than as recommended by the manufacturer

DISCLAIMER: Information presented within this technical specification was correct on date of issue. Information may be subject to change without notice as part of ongoing product improvement and development. To confirm any specific piece of information shown is current please email technical@jspsafety.com.



















