


Fall arrest lanyard TWIN

**TECHNICAL
SPECIFICATION**


HEIGHT SAFETY

These Fall arrest lanyards come with the energy absorption feature incorporated within their core, They do not require any extra energy absorption pack, hence are lighter in weight.

FAR0405



Stitching pattern



METAL COMPONENTS

Material: Connectors in aluminium

Finish: Black

Breaking strength: 23 kN

DIMENSIONS

Size: 2 meters

Weight: 350 g (+- 10 g)

CLEANING & MAINTENANCE

Maintenance of this product must only be carried out by a trained and competent person who will:

Clean the product using the following procedure: using only warm water, using only mild detergent, using only a sponge or soft nylon brush, using fresh clean water to rinse the detergent off the product, drip dry the equipment allowing the product to thoroughly dry out before next use.

Ensure that NO alterations to the product are made.

Ensure that the following cleaning methods are NOT used: water over 40° C, bleach, any detergent not suitable for bare skin, wire brushes or other scouring agents, jet wash or other power products, radiators or other direct heat sources, ensure that a thorough visual and tactile examination of the product is made after cleaning, before the item is allowed to be re-used.

STITCHING THREAD

Material: High-tenacity polyester

WEBBING

Material: polyester tubular webbing

Width: 44+-1 mm

Breaking strength: 25 kN

CHARACTERISTICS

Twin elasticated lanyard with incorporated shock absorbing webbing.

1 quarter turn aluminium connector. Gate opening: 21 mm. Conforms to EN362:2004 Class B

2 aluminium scaffold hooks. Gate opening 60 mm. Conforms to EN362:2004 Class T

40 mm wide tubular polyester webbing with textile loops.

CONFORMITY

EN 355: 2002

The lifespan of the product is 10 years from the date of manufacture subject to passing necessary checks and inspection by a competent person.

Static strength: 15 kN for 3 Minutes.

Dynamic strength: Maximum breaking force does not exceed 6kN in the line when tested on a free fall from 4 meters height attached to a test mass of 100 kgs.



MANUFACTURING FOR SAFETY
WWW.JSPSAFETY.COM

UKSALES@JSP.CO.UK
TEL: +44 (0)1993 826050



Issued 31/10/2018, V2