

**PRODUCT SPECIFICATION & TECHNICAL DATA** 

## FP02 - Webbing Anchorage Sling

Collection: Anchorage Device Range: Fall Protection Materials: Polyester Inner Pack: 24 Outer Carton: 48



## **Product information**

Engineered using heavy duty polyester webbing for ultimate durability, the 2 metre webbing anchorage sling allows the user to create a safe and reliable connection point which adjusts to a wide variety of anchorage points.

#### **Anchorage Device**

Anchorage devices are common fall protection solutions in work areas that lack existing anchor points for personnel tie-off. They are certified to the EN 795 standard, making them approved anchor points for any elevated work area that poses a risk of fall to the worker. These points are responsible for connecting the user to a lifeline or lanyard making them must-haves for the safety of workers at height.

#### **Fall Protection**

Fall Protection is put in place to prevent the risks associated with falling from heights, reducing impact force, restricting obstacle/ground collision and restricting users from fall hazard areas. Portwest offer a full range of fall protection products for working at height.

## Standards

EN 795

## **Features**

- CE-CAT III
- Superior strength
- Ultra lightweight for long uses
- Quick and easy installation
- Suitable for a wide range of applications
- Max rated load 100kg



**PRODUCT SPECIFICATION & TECHNICAL DATA** 

# FP02 - Webbing Anchorage Sling Commodity Code: 5609000000

#### **Test House**

SATRA Technology Europe Ltd (Notified Body No.: 2777) Bracetown Business Park D15 YN2P, Ireland Cert No: 2777/13445-01/E00-00

SATRA Technology Centre Ltd (Notified Body No.: 0321) SATRA Technology Park NN16 8SD, United Kingdom Cert No: AB0321/17404-01/E00-00

#### **CARTON DIMENSIONS/WEIGHT**

| Item    | Colour | Len  | Wid  | Hgt  | Weight (Kg) | Cubic (m <sup>3</sup> ) | EAN13         | DUN14          |
|---------|--------|------|------|------|-------------|-------------------------|---------------|----------------|
| FP02YER | Yellow | 60.0 | 40.0 | 25.0 | 0.4900      | 0.0600                  | 5036108279852 | 15036108769893 |