

FP75 - Double 140kg 1.8m Lanyard with Shock Absorber

Collection: Lanyards

Range: Height Safety

Materials: Polyester Webbing, Alloy Steel, Heat Treated, Zinc

Outer Carton: 10

Product information

This double ended lanyard features a shock absorber, a scaffold hook and a snap hook. It is tested to withstand a 140KG user and is 180cm long including connectors when fully extended.

Lanyards

The Portwest collection of lanyards are for restraint, positioning and fall arrest systems. Available in different lengths and material types including rope, webbing and elasticated webbing for ultimate wearer choice.

Height Safety

Height Safety is put in place to prevent the risks associated with falling from heights, reducing impact force, restricting obstacle/ground collision and restricting users from fall hazard areas. Portwest offer a full range of Height Safety products for working at height.

Standards

EN 354:2010
EN 355:2002 (140KG)
EN 362:2004



Features

- Elasticated webbing reduces the risk of tripping or snagging
- 52mm scaffolding hook opening
- Gate opening 20mm
- Shock Absorbing
- Durable webbing with high breaking strength
- 10 Year shelf life from manufacturing date outlined in product label
- Max rated load 140kg
- Retail box which aids presentation for retail sales
- CE certified
- UKCA marked

FP75 - Double 140kg 1.8m Lanyard with Shock Absorber
Commodity Code: 5609000000

Test House

CCQS Certification Services Ltd. (Notified Body No.: 2834)
Block 1, Blanchardstown Corporate Park
D15 AKK1, Ireland
Cert No: CE-PC-191210-016-05-9C

Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m ³)	EAN13	DUN14
FP75K1R	Black/Orange	55.0	25.0	34.0	2.6600	0.0468	5036108327461	15036108816245