

Mk7[®]

STD PEAK - VENTILATED - SLIP RATCHET - RETRACTASPEC™

PRODUCT CODE: AHN120-10 _ _ 00

THE ULTIMATE IN EN 397 HEAD PROTECTION

TECHNICAL SPECIFICATION

HEAD PROTECTION

INSTRUCTIONS FOR USE

Fit helmet on head and fasten strap to ensure fit

For adequate protection this helmet must be worn with peak facing forward

Ensure the helmet is adjusted to the size of the user's head

WEBBING HARNESS:

HDPE Strap & Webbing Clips with Polyester Webbing Straps



SWEATBAND:

'Nomaz' Style
Leatherette Sweatband



SHELL:

Recyclable UV Stabilised HDPE



RETRACTASPEC™:

Integrated eyewear ensuring that eye protection is on hand when needed and never lost, whilst removing the need for additional eye protection. Protects to EN 166.1.F.

SLIP RATCHET:

EasyJust[®] Slip Ratchet



THE ULTIMATE IN HEAD PROTECTION

CLEANING & MAINTENANCE

The unit may be cleaned with soap and warm water and dried with a soft cloth

The helmet should not be cleaned with chemical or abrasive cleaners

The helmet should be stored out of direct sunlight

The helmet should be stored away from chemicals and extremes of temperature

CONFORMITY

Conforms to EN 397

EC Certificate Num. 00279, issued by BSI Product Certification

Wide size range

High comfort fit

Standard shell offers protection from -20°C to 50°C

Available in a choice of colours

Incorporates a rain channel

Company personalisation available by printing

Accessories available



MANUFACTURING FOR SAFETY
WWW.JSP.CO.UK

UKSALES@JSP.CO.UK
TEL: +44 (0)1993 826050



OXFORD, ENGLAND

Issued 21/04/16, V7

Mk7®

STD PEAK - VENTILATED - SLIP RATCHET - RETRACTASPEC™

PRODUCT CODE: AHN120-10 _ _ 00

THE ULTIMATE IN EN 397 HEAD PROTECTION

TECHNICAL SPECIFICATION

HEAD PROTECTION

DIMENSIONS OF OUTER PACKAGING

Quantity: 10

Weight: 5.49kg (Approx.)



HEIGHT:
466mm



HELMET FEATURES

EN STANDARD	EN397	Yes
PERFORMANCE	Impact Resistance	Yes 50 Joules
TEMPERATURE RESISTANCE	+50°C -20°C	Yes Yes
SHELL MATERIAL	HDPE Recyclable	Yes Yes
HARNESS MATERIAL	LDPE Textile	Yes Yes
OPTIONS	Universal Accessories Integrated Eyewear 2pts or 3pts Chinstrap Retractaspec	Yes Yes Yes Yes
HARNESS SYSTEM OPTIONS	Slip Ratchet 8 pts	Yes Yes
LOGO OPTIONS	Front Rear Side MOQ Logo Individual Name	Yes Yes Yes 10 Yes

WIDTH:
255mm

LENGTH:
590mm

DIMENSIONS OF HELMET

Length: 296mm

Width: 224mm

Height: 164mm

Weight: 435g (Approx.)



HELMET COLOURS

Insert the following two digit number in place of the dashes in the product code of your desired helmet



01 White 02 Yellow 03 Green 05 Blue 06 Red 08 Orange

LIMITATIONS OF USE

Protection will only be offered if the helmet is fitted correctly

Any helmet subjected to severe impact should be replaced immediately. Do not apply paint, solvents or adhesive labels except in accordance with instructions from the manufacturer

The harness, when in contact with the skin may cause allergic reactions to susceptible individuals. If this occurs leave the hazard area, remove the helmet and seek medical advice

The attention of users is also drawn to the dangers of modifying or removing any of the original component parts, other than as recommended by the manufacturer



MANUFACTURING FOR SAFETY
WWW.JSP.CO.UK

UKSALES@JSP.CO.UK
TEL: +44 (0)1993 826050



Issued 21/04/16, V7