

TECHNICAL DATA SHEET

SF89 MADISON LADIES BOOT



DESCRIPTION

Moulded specifically for ladies' feet, the Madison boot features a water resistant leather upper to keep feet dry plus padded ankle support. It has both steel toe cap and midsole protection and the hardwearing, dual density PU sole is shock absorbent, anti-slip, anti-static and fuel oil resistant.

SIZES

UK 2-8

STANDARDS

EN20345 S3 SRC

KEY FEATURES

- Water resistant leather upper with padded ankle
- Steel toe cap and midsole
- Dual density shock absorbent, anti-slip, anti-static and fuel oil resistant PU sole
- Energy absorbing heel reduces foot fatigue

FEATURE ICONS



TECHNICAL DATA SHEET

MATERIALS

- Leather upper
- PU/PU sole
- Steel toe cap
- Steel midsole

TYPICAL INDUSTRIES

- Automotive
- Uniform
- Facilities management
- Security
- Emergency services
- Transport
- Warehousing

CERTIFICATION/MARKINGS



EN ISO 20345:2011 is an internationally recognised standard which specifies requirements for safety footwear. Any product which references an EN standard must have the relevant certification attributed to the product code found on the product.

The product standard can be found on the tongue label and should match that stated on the certification. The standard is usually a group of numbers and letters, for example S3 WR HRO SRC. These letters and numbers denote the characteristics that make up the footwear you are buying which include properties such as protective toe cap, water-resistant uppers, protective midsole, fuel oil resistance, anti-static, heat resistance and slip resistance.

Users are advised to select the required class of performance based on the risk assessment of the location and/or task as appropriate.

PRODUCT DETAILS

CODE	SIZE	COLOUR	BARCODES	PACKAGING
SF8902	2	Black	5019200292134	Each pair individually boxed Purchase multiple: 1 Outer carton quantity: 10 
SF8903	3	Black	5019200292141	
SF8904	4	Black	5019200292158	
SF8905	5	Black	5019200292165	
SF8906	6	Black	5019200292172	
SF8907	7	Black	5019200292189	
SF8908	8	Black	5019200292196	