

TG6240

Conforming to cut level E under the new EN388:2016 standard, TG6240 has unrivalled levels of dexterity and comfort and is designed to last for long periods of time.

The MicroDex Ultra coating and new Life Extending Technology makes the TG6240 perfect for high cut risk tasks in wet, dry and oily conditions. Also features a thumb crotch to further extend the wear life of the glove.

The LXT range is certified as carbon neutral. This means that at no extra cost, your LXT glove has zero negative impact on the environment, to the point of delivery.

Ideal for

- Automotive
- Construction and utility
- Engineering and manufacturing
- Oil and gas
- Rail
- Mechanical and electrical
- Waste, recycling and local authority



EN 388	4X44E
Sizes	6-11
Liner	Polyester/Glass HPPE/Steel/ Nylon/Elastane
Gauge	15gg
Coating	MicroDex Ultra
Conditions	   

EN 388:2016



4 X 4 4 E



EN 407:2020



X 1 X X X X

Qty/band 10 pairs

Qty/carton 100 pairs



KEY



Dry



Wet



Heat



Oily



Cold



Chemical



Net zero carbon footprint



Plastic free packaging



Conforms to EN 407:2020



Resistance to oil & water



Reduction in cost in usage



Comfort & durability



Washable to 40°C
Certified up to 3 washes



Reduction in waste & landfill

0.7391 KgCO₂e /pair
(Prior to carbon inset)